



On-Ground Concrete Cementitious Bond Coat, Ceramic Tile	CPF113-23C TCNA F113-23* <small>*Refer to TCNA for complete guidelines</small>
Project Name:	Date:

Service Rating: Extra Heavy
Environmental Exposure Classifications: Res1, 2, 3, 5; Com1, 2, 3, 5

*USE OF A MEMBRANE IS OPTIONAL

NOT TO SCALE

- ### TCNA Minimum Requirements
- Cementitious Bond Coat:
 - With crack isolation membrane: ANSI A118.4
 - Without crack isolation membrane: ANSI A118.1
 - Cementitious Grout: ANSI A118.6 or better

- ### CementPro Products
- Cementitious Bond Coat Options:**
 - » With crack isolation membrane:
 - Multi Pro
 - Maxibond Pro
 - Maxibond Pro LFT
 - » Without crack isolation membrane:
 - Thin-Set Pro
 - Cementitious Grout Options:**
 - Poly-Pro Sanded Grout
 - Poly-Pro Non-Sanded Grout

The specifications and content presented within this document are provided by CementPro solely as a reference and informational resource. Prior to using any CementPro product, it is the user's absolute responsibility to thoroughly read and strictly follow the safety warnings, instructions and technical data provided in the product's current Technical Data Sheet (TDS), product label and Material Safety Data Sheet (MSDS). These documents are readily available at www.cementpro.com or by calling 1-951-300-0300. While some content within this document may reflect or borrow elements from industry resources such as the Tile Council of North America (TCNA) Handbook for Ceramic, Glass, and Stone Tile Installations, it is crucial to refer to the original handbook itself for comprehensive and authoritative information. CementPro reserves the right to update or modify this disclaimer at any time without prior notice. Please refer to this document regularly for the latest information.



On-Ground Concrete Cementitious Bond Coat, Glass Tile	CPF113-23G TCNA F113-23* <small>*Refer to TCNA for complete guidelines</small>
Project Name:	Date:

Service Rating: Extra Heavy
Environmental Exposure Classifications: Res1, 2, 3, 5; Com1, 2, 3, 5

Glass Tile
 1 // Cementitious Bond Coat
 Optional Membrane*
 2 // Cementitious Grout
 Concrete, On-Ground

*USE OF A MEMBRANE IS OPTIONAL
NOT TO SCALE

TCNA Minimum Requirements

1. Cementitious Bond Coat:
 - With crack isolation membrane: ANSI A118.4
 - Without crack isolation membrane: ANSI A118.1
2. Cementitious Grout: ANSI A118.6 or better

CementPro Products

1. **Cementitious Bond Coat Options:**
 - » With crack isolation membrane:
 - Glass Pro
2. **Cementitious Grout Options:**
 - Vivid Pro Grout

The specifications and content presented within this document are provided by CementPro solely as a reference and informational resource. Prior to using any CementPro product, it is the user's absolute responsibility to thoroughly read and strictly follow the safety warnings, instructions and technical data provided in the product's current Technical Data Sheet (TDS), product label and Material Safety Data Sheet (MSDS). These documents are readily available at www.cementpro.com or by calling 1-951-300-0300. While some content within this document may reflect or borrow elements from industry resources such as the Tile Council of North America (TCNA) Handbook for Ceramic, Glass, and Stone Tile Installations, it is crucial to refer to the original handbook itself for comprehensive and authoritative information. CementPro reserves the right to update or modify this disclaimer at any time without prior notice. Please refer to this document regularly for the latest information.